



DC 200

DEEP CYCLE BATTERY
12V | 200Ah | 100h

Electrical Specifications

Nominal voltage	12V
Rated capacity	200Ah at C ₁₀₀
Separator	PE
Cycle life in relation to depth of discharge	700 cycles at 30 % DoD
	400 cycles at 50 % DoD
	280 cycles at 80 % DoD
	180 cycles at 100 % DoD

Mechanical Specifications

Measurements (L x W x H)	513 x 223 x 223mm
Approx. weight	46.8kg
Terminal type	Round
Case Material	PP
Lid Material	PP


Charging and Discharging

Capacity C ₁₀₀	200Ah
Capacity C ₂₀	180Ah
Capacity C ₁₀	160Ah
Capacity C ₅	155Ah
Max. charge current	35A
Max. discharge current	1765A (5 seconds)


Temperature Specifications

Discharge Temperature	-15 to 50°C
Charge Temperature	0 to 40°C
Storage Temperature	-15 to 50°C
Normal Operating Temperature	25 ± 5°C


Measurements




Discharge Characteristics Curve




Charge Characteristics Curve For Cycle Use (IU)




Relationship of Cycle Life and DoD




Relationship of Charge Voltage and Temperature




Temperature Effects on Capacity



Storage Characteristics



Effect of Temperature on Long-Term Life



Relationship of OCV and State of Charge

